

# Fiber-Optic Receiver

Rev 2.0



## OPT-RX16-RS485U(C) Fiber-Optic Receiver

### Key Features

- 16ch Optic to HD-SDI converter
- LC type 16ch Fiber-optic input, BNC 16ch output
- Supports SMPTE-292M(HD-SDI) video standard
- Supports 1080p30/25, 720p25/30/50/60 resolution
- Up to 20Km video/data(RS485) transmission via single-mode cable
- Power, Video, Data, Optic status LED indicators
- 19" Rack-mount type
- 'UC' model has HDcctv certificate

### Specifications

#### HD-SDI PORT

Video standard	SMPTE292M
Resolution	SMPTE 274M(1080p30/25) SMPTE 296M(720p25/30/50/60)

#### OPTICAL PORT

Fiber Type	Single-mode
Connector	LC
Distance	20Km(12.4mi) at 1.5Gbps

#### ENVIRONMENTAL & PHYSICAL

Dimension	483(W) x 342(D) x 44(H) mm
Weight	Approx. 4.5Kg(9.92lbs)
Operating temperature	0°C to 50°C / 20% to 80%RH
Input voltage	DC12V
Power consumption	Max. 30W
Approval	KC, FCC, CE, RoHS, HDcctv

### Dimension (Unit : mm)

