

- · Power Supply and Control over One Coax Cable (PoC and CoC)
- · PoC: 48V (Base model) or 24V (*-24V model)
- · 2.1 Megapixel SONY STARVIS Sensor
- · HD-SDI / EX-SDI / EX-SDI2.0 Selectable
- · DC Iris, 2.7mm~12mm Megapixel 2 Motor Lens
- \cdot One-push Auto Focus, Zoom/Focus Control
- · 3DNR (Noise Reduction)
- \cdot Back Light Compensation (WDR / BLC / HLC)
- · True Day&Night (ICR)
- · Removing Fog (Defog)
- · Privacy Masking (10 zones)
- · Smart IR (No Saturation)
- \cdot IP68 Level Protection against Dust and Water
- · Internal IR LED: 18 pcs

*** How to select Video Output Format**

Remove cover and use OSD control lever

- Up>Up>Up>Enter : HD-SDI
- Down>Down>Enter : EX-SDI Left>Left>Left>Enter : EX-SDI 2.0

Ø 133

5



Specification

Description		NTSC	PAL		
Sensor Type		2.1 Megapixel SONY STARVIS CMOS Sensor			
Total Pixels		1920 (H) × 1080 (V) = 2.1M pixels			
Scanning System		Progressive Scan			
Lens	Filter	True Day & Night (ICR)			
	Type	2.7~12mm DC IRIS VARIFOCAL 2 Motor LENS (ICR)			
Video	Output	1 (BNC 1.0 Vp-p, 75Ω)			
	Resolution	1080p30 1080p25			
	Format	HD-SDI / EX-SDI / EX-SDI2.0 selectable			
Video Control	AGC	LEVEL 0~10			
	S/N Ratio	more than 52dB			
	Back Light Compensation	OFF / HLC / BLC / WDR			
	ACE	OFF / LOW / MIDDLE / HIGH			
	Min. Illumination	BW: 0.0005Lux@50IRE, F1.3, 3100K, DSS(OFF), AGC(10)			
		Color: 0.008Lux@50IRE,F1.3, 3100K, DSS(OFF),			
	DNR	AGC(10) OFF / LOW / MIDDLE / HIGH			
	Iris Adjust.	DC / Manual			
	White Balance	AUTO / AUTOext / PRESET / MANUAL			
	Electric Shutter	INDOOR / OUTDOOR / INDOOR-ANTI-BLUR /			
		OUTDOOR-ANTI-BLUR / FLICKER / MANUAL (11 Steps)			
	OSD Language	ENG			
	Day&Night	COLOR / BW / EXTERN / AUTO			
	Defog	OFF / ON (AUTO, MANUAL-LOW/MIDDLE/HIGH)			
	Privacy	OFF / ON (Programmable 10 zones)			
	DSS	OFF / AUTO / X2~X32			
	Digital Effect	OFF / H-MIRROR / V-MIRROR			
	IR LED	18 pcs			
	Smart IR	OFF / ON			
0	SD Control	OSD Key / CoC (UCC-A)			
PoC Input Voltage		Base Model: DC48V±10%, *-24V Model: DC24V±10%			
Power Consumption		IR OFF: 2.7W (MAX) / IR ON: 5.5W (MAX)			
Operation Temp./Humidity		-10°C~ +50°C / MAX 90% RH			
Storage Temp./Humidity		-20°C ~ +60°C / MAX 90% RH			
Certifications		FCC, CE			

Warranty

					Warranty Term : 2 Years
Product Name	HD-CCTV Camera		Model Name	K1080PVD-SIR18-AF/AF-24V	
			Serial No.		
Purchase	(Year)	(Month)	(Date)	Customer	
Address					(TEL.)
Dealer				Representtative	

Please fill out vacant area before selling products.

★ For customer service ★

Please read through product manual before claiming customer service.

Any simple malfunctions due to customer's misunderstanding on the product will be fixed by customer's side.

For requesting service?

Please inform details of malfunctions correctly.

Free or non free repair will be decided based on details of warranty card.

WebGate Inc.

6F Hanlim Venture Town B/D 284 Gongdanro Gunpo Gyeonggido, 435-862 Korea

: TEL : +82-31-428-9300

The damage coming from following condition will be repaired at customer's cost.


- 1) Any damage comes from customer's carelessness.
- 2) In case not recommended power is entered.
- 3) In case user repair unit at their own.
- 4) Any damage comes from natural disaster (Fire, Flood, etc)
- 5) Consumable parts replacement.

Tech Note

One Cable Solution Power supply and Control over One Coax Cable

PoC(Power over Coax): Only one Coax Cable is required to supply power. Do not require any power line.CoC(Control over Coax): Only one Coax Cable is required to control camera. Do not require RS485 line.

Non-PoC: Additional power line and RS485 line is required



Grade A (Commercial broadcasting and nunications equipment)

The product is a device obtained EMC registration for commercial (A grade). Distributors and users should be aware of this point, and it is sed for purposes outside of the home

WEBGATE **HD-CCTV** solution provider



Premium to your HD-CCTV solution